



SAFETY DATA SHEET FULLGEAR CT 50

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name FULLGEAR CT 50

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Multifunctional transmission - gear oil. Please look at the Technical Data Sheet of the product for further information.

1.3. Details of the supplier of the safety data sheet

Supplier OPET FUCHS MADENİ YAĞ SAN. ve TİC. A.Ş.
Atatürk Organize Sanayi Bölgesi 10006 Sok.
No:12 35620 Çiğli/İZMİR
Tel: +90 232 376 78 38
Fax: +90 232 376 78 39

1.4. Emergency telephone number

Emergency telephone UZEM (National Poison Consultancy Center): 114
Emergency Health Service:112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified
Health hazards Eye Irrit. 2 - H319
Environmental hazards Aquatic Chronic 3 - H412

2.2. Label elements

Pictogram



Signal word Warning

Hazard statements H319 Causes serious eye irritation.
H412 Harmful to aquatic life with long lasting effects.
EUH208 Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivatives, calcium salts. May produce an allergic reaction.

FULLGEAR CT 50

Precautionary statements	<p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
---------------------------------	--

2.3. Other hazards

By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

zinc dithiophosphate	1-5%
CAS number: 4259-15-8	EC number: 224-235-5
Classification	
Eye Dam. 1 - H318	
Aquatic Chronic 2 - H411	
Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivatives, calcium salts	<1%
CAS number: 722503-68-6	EC number: 682-816-2
Classification	
Skin Sens. 1B - H317	
Aquatic Chronic 4 - H413	
Phenol, dodecyl-, branched	<1%
CAS number: 121158-58-5	EC number: 310-154-3
M factor (Acute) = 10	M factor (Chronic) = 10
Classification	
Skin Corr. 1C - H314	
Eye Irrit. 2 - H319	
Repr. 1B - H360	
Aquatic Acute 1 - H400	
Aquatic Chronic 1 - H410	

The full text for all hazard statements is displayed in Section 16.

Composition comments	<p>Note L: The product contain special performance additives and base oils which are considered to be severely refined and not considered to be carcinogenic. All of the base oils in the product have been demonstrated to contain less than 3% (w/w) dimethyl sulfoxide extract by the IP 346 test.</p>
-----------------------------	---

SECTION 4: First aid measures

4.1. Description of first aid measures

FULLGEAR CT 50

General information	Change clothes and shoes contaminated or soaked by product. Never put rags contaminated by product into cloth-pockets. Get medical attention if any discomfort continues. Not expected to give rise to an acute hazard under normal conditions of use.
Inhalation	Remove affected person from source of contamination and immediately take outside to fresh air. Consult a doctor if any discomfort continues.
Ingestion	IF SWALLOWED: Rinse mouth thoroughly with water. Get medical attention immediately. Do not induce vomiting unless under the direction of medical personnel. Never give anything by mouth to an unconscious person. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Show this Safety Data Sheet to the medical personnel.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water. Continue to rinse for at least 15 minutes. Brush off loose particles from skin. If adhesive bonding occurs, do not force skin apart. Get medical attention.
Eye contact	Do not rub eye. Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention if symptoms are severe or persist after washing.
Protection of first aiders	Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	No specific symptoms known.
Ingestion	No specific symptoms known.
Skin contact	No specific symptoms known.
Eye contact	No specific symptoms known.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Symptomatic treatment should be applied. In case of excessive inhalation of the product vapor may lead to lung inflammation (chemical pneumonitis). Dermatitis may result from prolonged or repeated exposure.
Specific treatments	Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Use Film-Making Foam Concentrate (A.F.F.F.) to extinguish the burning product. If not available, extinguish with dry chemical powder due to the size of fire. If the product is in pressurized container, cool with water spray jet.
Unsuitable extinguishing media	During a fire, DO NOT extinguish by applying pressurized water and water jet directly on the burning product. Use water fog to cool down.

5.2. Special hazards arising from the substance or mixture

Specific hazards	This product is not explosive. Do not heat up near flash point.
Hazardous combustion products	In case of fire toxic and corrosive gases may form. These gases: Carbon dioxide, carbon monoxide, sulphur oxides, phosphorus oxides, metal oxides

5.3. Advice for firefighters

FULLGEAR CT 50

Protective actions during firefighting	In case of fire, shut off flow if it can be done without risk. Stop leak if safe to do so. Move undamaged containers from fire area if it can be done without risk. Prevent the burning product from entering into drainage system to avoid release of the product. To prevent spreading of the product build-up binders or barriers by using non-burning material such as sand. Use air-supplied respirators to protect against gases/fumes in case of fire-fighting.
Special protective equipment for firefighters	Fire-fighting should be done by trained personnel. Special protective full-clothing, air-supplied respirator, gloves and protective goggles should be worn. Dry chemical sand used for fire extinguishing and other fire extinguishing equipment should meet the national and international standards.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	In case of spills, beware of slippery floors and surfaces. Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. For personal protection, see Section 8. Do not smoke, use open fire or other sources of ignition. Wear protective gloves and (in case of splashes) goggles/face shield too.
-----------------------------	--

6.2. Environmental precautions

Environmental precautions	Avoid release to the environment. Avoid discharge into drains, water courses or onto the ground. To prevent release, place container with damaged side up. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to local appropriate regulatory body. Empty container contains product residue which may exhibit hazards of product.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Large Spillages: Stop leak if possible without risk. DO NOT touch spilled material! Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13. Avoid the spillage or runoff entering drains, sewers or watercourses. Inform authorities if large amounts are involved. Small Spillages: Stop leak if possible without risk. Dam and absorb spillage with sand, sawdust or other absorbent. Absorb in vermiculite, dry sand or earth and place into containers. Dispose of via an authorised person/licensed waste disposal contractor in accordance with local regulations.
--------------------------------	---

6.4. Reference to other sections

Reference to other sections	For handling and storage, see section 7. For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.
------------------------------------	--

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions	Provide adequate ventilation. Container must be kept tightly closed when not in use. Protect against direct sunlight. Do not heat up the product near flash point. Avoid spilling, skin and eye contact. Avoid eating, drinking and smoking when using the product. Persons susceptible to allergic reactions should not handle this product.
Advice on general occupational hygiene	Wash after use and before eating, smoking and using the toilet. Take off contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions	Store in a demarcated bunded area to prevent release to drains and/or watercourses. Store in accordance with local regulations. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Protect from freezing and direct sunlight. Store in closed original container at temperatures between 0°C and 50°C. Keep away from food, drink and animal feeding stuffs.
----------------------------	---

FULLGEAR CT 50

Storage class	Not special storage precautions required.
7.3. Specific end use(s)	
Usage description	For containers or container linings,use mild steel or high density polyethylene (HDPE). For containers or container linings,avoid PVC. Polyethylene containers should not be exposed to high temperatures because of possible risk distortion.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Ingredient comments No exposure limits known for ingredient(s).

8.2. Exposure controls

Protective equipment



Appropriate engineering controls	Provide adequate ventilation. Avoid inhalation of vapours. In case of insufficient ventilation, wear suitable respiratory equipment. Observe any occupational exposure limits for the product or ingredients.
Personal protection	In case of splashing or scattering, wear protective oil-resistant or chemical-resistant clothing.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended. Use thin cotton gloves inside the rubber gloves if allergy risk. The selection of suitable gloves does not only depend on the material, but also on further marks of quality varies from manufacturer. As the product is a pereparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
Other skin and body protection	Use skin protection cream for preventive skin protection. Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.
Hygiene measures	Provide eyewash station. Do not smoke in work area. Wash hands after contact. Promptly remove non-impervious clothing that becomes contaminated. Contaminated clothing should be placed in a closed container for disposal or decontamination. Remove contaminated clothing and wash the skin thoroughly with soap and water after work. When using do not eat,drink or smoke.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator fitted with the following cartridge: High-efficiency particulate filter.
Thermal hazards	Contact with hot product can cause serious thermal burns. If there is a risk of contact with hot product, all protective equipment worn should be suitable for use with high temperatures.

FULLGEAR CT 50

Environmental exposure controls	<p>STEL: 10mg/m³ 15 minutes. Form: Oil mist, mineral</p> <p>TWA: 5mg/m³ 8 hours. Form: Oil mist, mineral</p> <p>Short-Term Exposure Limit (STEL). The National Institute for Occupational Safety and Health (NIOSH,1992).</p> <p>Time-Weighted Average (TWA). Occupational Safety and Health Administration (OSHA, 29 CFR 1910.1000,Table Z-1).</p>
--	---

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Clear Liquid
Colour	Brown.
Odour	Mild, oily.
Flash point	264°C
Bulk density	0,907 kg/l
Solubility(ies)	Insoluble in water.
Partition coefficient	Not known.
Auto-ignition temperature	Not self-ignited
Viscosity	217,1 mm ² /s @ 40°C
Explosive properties	Not considered to be explosive.
Oxidising properties	Does not meet the criteria for classification as oxidising.
Comments	Values are typical. These values may be variable within the product specification.

9.2. Other information

Other information	No information required.
--------------------------	--------------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	No test data specifically related to reactivity available for this product or its ingredients.
-------------------	--

10.2. Chemical stability

Stability	Stable at normal ambient temperatures. Mixing with any other material.
------------------	--

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	No potentially hazardous reactions known.
---	---

10.4. Conditions to avoid

Conditions to avoid	Avoid freezing. Avoid contact with strong oxidising agents. Avoid exposure to high temperatures or direct sunlight. Keep away from moisture.
----------------------------	--

10.5. Incompatible materials

Materials to avoid	Strong oxidising agents. Strong acids.
---------------------------	--

10.6. Hazardous decomposition products

FULLGEAR CT 50

Hazardous decomposition products Does not decompose when used and stored as recommended. Heating may generate the following products: Toxic and corrosive gases or vapours. Thermal decomposition or combustion products may include the following substances: Carbondioxide,carbon monoxide,sulphur oxides,phosphorus oxides,metal oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects	No data recorded.
Other health effects	No data available to indicate product or any components are carcinogenic,mutagenic,genotoxic,and chronic health hazards.
<u>Skin corrosion/irritation</u>	
Skin corrosion/irritation	Mevcut özel test verisi yoktur.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Causes serious eye irritation.
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	No specific test data are available.
<u>Skin sensitisation</u>	
Skin sensitisation	No specific test data are available.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	No specific test data are available.
<u>Carcinogenicity</u>	
Carcinogenicity	No specific test data are available.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	No specific test data are available.
Reproductive toxicity - development	Mevcut özel test verisi yoktur.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	No specific test data are available.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	No specific test data are available.
<u>Aspiration hazard</u>	
Aspiration hazard	No specific test data are available
General information	Information given is based on a knowledge of the components and the toxicology of similar products.
Inhalation	Not expexted to cause irriation. Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing.
Ingestion	May cause discomfort if swallowed. The main symptoms are gastrointestinal ailments, including upset stomach.
Skin contact	Skin irritation should not occur when used as recommended. Repeated exposure may cause skin dryness or cracking. May cause sensitisation or allergic reactions in sensitive individuals.
Eye contact	Not expexted to cause eye irriation. Vapors formed from heating may cause eye irriation.

FULLGEAR CT 50

Acute and chronic health hazards	The product contain special performance additives and mineral base oils which are considered to be severely refined and not considered to be carcinogenic. All of the base oils in the product have been demonstrated to contain less than 3% (w/w) dimethyl sulfoxide extract by the IP 346 test. USED OILS are more dangerous than new oils. Used oils may contain hazardous components which have the potential to cause skin cancer.
Route of entry	Inhalation, ingestion, skin, eye contact.
Target organs	Skin, eyes, respiratory system, lungs, gastro-intestinal tract.
Medical symptoms	This product contains para-dodecylphenol. Rats given high, repeated daily doses of para-dodecylphenol by oral intubation experienced adverse reproductive effects. The relevance of these effects to humans is uncertain.
Medical considerations	This product contains para-dodecylphenol. Pregnant rats given high, repeated daily doses of para-dodecylphenol by oral intubation gave birth to pups with cleft palate and skeletal malformations. The relevance of these effects to humans is uncertain.

SECTION 12: Ecological Information

Ecotoxicity	Harmful to aquatic life with long lasting effects.
<u>12.1. Toxicity</u>	
Toxicity	There is no specific test data available
<u>12.2. Persistence and degradability</u>	
Persistence and degradability	There are no data on the degradability of this product.
<u>12.3. Bioaccumulative potential</u>	
Bioaccumulative potential	No data available on bioaccumulation.
Partition coefficient	Not known.
<u>12.4. Mobility in soil</u>	
Mobility	The product is insoluble in water and will spread on the water surface. It may be absorbed by soil and will not be mobile.
<u>12.5. Results of PBT and vPvB assessment</u>	
Results of PBT and vPvB assessment	There is no specific test data available.
<u>12.6. Other adverse effects</u>	
Other adverse effects	Not known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	Empty packages and wastes produced after the usage of the product should be taken under control according to the current environmental regulations. Unless otherwise noted all wastes should be evaluated as hazardous waste.
Disposal methods	Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements.
Waste class	13 02 06*Synthetic engine, gear and lubricating oils 13 02 08*other engine, gear and lubricating oils

FULLGEAR CT 50

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Observe the general safety regulations when handling chemicals. The product is not subject to identification regulations under EC Directives until 2004/73/EC (31. ATP) and the Ordinance on Hazardous Materials. The concentrations of the dangerous compounds, which are possibly specified under point 3, are not above the value for classification. Local regulations must be kept.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information

All ingredients are listed in the European Inventories. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. This data sheet is a safety data sheet according to 91/155/EU. For products which are not subject to classification according to EU lists this data sheet is made on a voluntary base.

FULLGEAR CT 50

Key literature references and sources for data	December 13, 2014, No. 29204, "the Ministry of Environment and the Ministry of Urban Development Related to Safety Data Sheets on Hazardous Substances and Mixtures Direction"
Revision comments	Revised classification.
Issued by	AYŞEGÜL SÜER MSc. R&D Engineer Certified by NBC for MSDS (Certificate No: 01.42.05) Opet Fuchs Madeni Yağ Sanayi ve Ticaret A.Ş. AOSB Mustafa Kemal Bulvarı No:12 35620 Çiğli/İZMİR E-Mail: Aysegul.SUER@opetfuchs.com.tr
Revision date	22/08/2017
Revision	5
Supersedes date	06/12/2010
SDS number	OPET.GBF.0922
Hazard statements in full	H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H360 May damage fertility or the unborn child if swallowed. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. H413 May cause long lasting harmful effects to aquatic life. EUH208 Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivatives, calcium salts. May produce an allergic reaction.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information contained in this data sheet. OPET FUCHS MADENİ YAĞ SAN. VE TIC. A.Ş. shall not be responsible for any injury or damage resulting from the abnormal use of the product, recipient assumes all such risks.