

SAFETY DATA SHEET FULLGEAR FD 10W-30

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name FULLGEAR FD 10W-30

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Çok Amaçlı Traktör Transmisyon Yağı. Detaylı bilgi için Teknik Bilgi Formuna başvurulmalıdır.

1.3. Details of the supplier of the safety data sheet

Supplier OPET FUCHS MADENÍ YAĞ SAN. ve TİC. A.Ş.

Atatürk Organize Sanayi Bölgesi 10006 Sok.

No:12 35620 Çiğli/İZMİR Tel: +90 232 376 78 38 Fax: +90 232 376 78 39

1.4. Emergency telephone number

Emergency telephone UZEM (National Poison Consultancy Center): 114

Emergency Health Service:112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Eye Irrit. 2 - H319

Environmental hazards Aquatic Chronic 3 - H412

Human health No specific hazards under normal use conditions. USED ENGINE OILS are more dangerous

than new engine oils. Used engine oils may contain hazardous components which have the potential to cause skin cancer. May cause skin sensitisation or allergic reactions in sensitive

individuals.

EnvironmentalThe product contains/contain a substance/substrances which is harmful to aquatic organisms

and which may cause long term adverse effects in the aquatic environment.

Physicochemical The product is not classified as flammable, but at a temperature above the flash point is

flammable when exposed to flame sources.

2.2. Label elements

Pictogram



Signal word Warning

Hazard statements H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

EUH208 Contains C14-18 alpha-olefin epoxide, reaction products with boric acid, Triphenyl

phosphite. May produce an allergic reaction.

Precautionary statements P264 Wash contaminated skin thoroughly after handling.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/ attention.

P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Mineral oil 1-5%

CAS number: —

Classification

Asp. Tox. 1 - H304

zinc dithiophosphate 1-5%

Classification

Eye Dam. 1 - H318 Aquatic Chronic 2 - H411

C14-18 alpha-olefin epoxide, reaction products with boric

<1%

acid

CAS number: -

Classification

Skin Sens. 1B - H317

Triphenyl phosphite <1%

CAS number: 101-02-0 EC number: 202-908-4

M factor (Acute) = 1 M factor (Chronic) = 1

Classification

Acute Tox. 4 - H302 Skin Irrit. 2 - H315

Eye Irrit. 2 - H319

Skin Sens. 1 - H317

Aquatic Acute 1 - H400

Aquatic Chronic 1 - H410

The full text for all hazard statements is displayed in Section 16.

Composition comments Note L: The product contain special performance additives and base oils which are

considered to be severely refined and not considered to be carcinogenic. All of the base oils in the product have been demonstrated to contain less than 3% (w/w) dimethyl sulfoxide extract

by the IP 346 test.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Get medical attention if any discomfort continues. Not expected to give rise to an acute

hazard under normal conditions of use.

Inhalation Remove affected person from source of contamination and immediately take outside to fresh

air. Consult a doctor if any discomfort continues.

Ingestion Remove affected person from source of contamination. Get medical attention immediately. Do

not induce vomiting unless under the direction of medical personnel.

Skin contact Remove affected person from source of contamination. Remove contaminated clothing

immediately and wash skin with soap and water. Continue to rinse for at least 15 minutes. Get

medical attention.

Eye contact Do not rub eye. Remove any contact lenses and open eyelids wide apart. Get medical

attention immediately. Rinse cautiously with water for several minutes.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation No specific symptoms known.

IngestionNo specific symptoms known.Skin contactNo specific symptoms known.

Eye contact No specific symptoms known.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Symptomatic treatment should be applied. In case of excessive inhalation of the product

vapor may lead to lung inflammation (chemical pneumonitis). Dermatitis may result from

prolonged or repeated exposure.

Specific treatments Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use Film-Making Foam Concentrate (A.F.F.F.) to extinguish the burning product. If not

available, extinguish with dry chemical powder due to the size of fire. If the product is in

pressurized container, cool with water spray jet.

Unsuitable extinguishing

media

During a fire, DO NOT extinguish by applying pressurized water and water jet directly on the

burning product. Use water fog to cool down.

5.2. Special hazards arising from the substance or mixture

Specific hazards In case of fire, toxic and corrosive gases may be formed. These gases: Carbondioxide,carbon

monoxide, sulphur oxides, phosphorus oxides, metal oxides This product is not explosive.

5.3. Advice for firefighters

Protective actions during firefighting

In case of fire, shut off flow if it can be done without risk. Stop leak if safe to do so. Move undamaged containers from fire area if it can be done without risk. Prevent the burning product from entering into drainage system to avoid release of the product. To prevent spreading of the product build-up binders or barriers by using non-burning material such as sand. Use air-supplied respirators to protect against gases/fumes in case of fire-fighting.

Special protective equipment for firefighters

Fire-fighting should be done by trained personnel. Special protective full-clothing, air-supplied respirator, gloves and protective goggles should be worn. Dry chemical sand used for fire extinguishing and other fire extinguising equipment should meet the national and international standards

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

In case of spills, beware of slippery floors and surfaces. Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. For personal protection, see Section 8. Do not smoke, use open fire or other sources of ignition. Wear protective gloves and (in case of splashes) goggles/face shield too.

6.2. Environmental precautions

Environmental precautions

Avoid release to the environment. Avoid discharge into drains, water courses or onto the ground. To prevent release, place container with damaged side up. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to local appropriate regulatory body. Empty container contains product residue which may exhibit hazards of product.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Large Spillages: Stop leak if possible without risk. DO NOT touch spilled material! Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13. Avoid the spillage or runoff entering drains, sewers or watercourses. Inform authorities if large amounts are involved. Small Spillages: Stop leak if possible without risk. Dam and absorb spillage with sand,sawdust or other absorbent. Absorb in vermiculite, dry sand or earth and place into containers. Dispose of via an authorised person/licensed waste disposal contractor in accordance with local regulations.

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Provide adequate ventilation. Container must be kept tightly closed when not in use. Protect against direct sunlight. Avoid spilling, skin and eye contact. Avoid eating, dringking and smoking when using the product. Persons susceptible to allergic reactions should not handle this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Protect from

freezing and direct sunlight. Store in closed original container at temperatures between 0°C

and 50°C.

Storage class Not special storage precautions required.

7.3. Specific end use(s)

Usage description For containers or container linings, use mild steel or high density polyethylene (HDPE). For

containers or container linings, avoid PVC. Polyethylene containers should not be exposed to

high temperatures because of possible risk distortion.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Ingredient comments

No exposure limits known for ingredient(s).

8.2. Exposure controls

Protective equipment





Appropriate engineering controls

Avoid inhalation of vapours. Observe any occupational exposure limits for the product or

ingredients. Provide adequate ventilation.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible. The following protection should be worn: Chemical splash goggles or

face shield.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

> a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended. Use thin cotton gloves inside the rubber gloves if

allergy risk.

Other skin and body

protection

Wear steel toe-cap shoes. Wear an apron.

Hygiene measures Provide eyewash station. Do not smoke in work area. Wash hands after contact. Promptly

> remove non-impervious clothing that becomes contaminated. Contaminated clothing should be placed in a closed container for disposal or decontamination. Remove contaminated clothing and wash the skin thoroughly with soap and water after work. When using do not

eat, drink or smoke.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator

fitted with the following cartridge: High-efficiency particulate filter.

Environmental exposure

controls

Colour

STEL: 10mg/m3 15 minutes. Form: Oil mist, mineral TWA: 5mg/m³ 8 hours. Form: Oil mist, mineral

Short-Term Exposure Limit (STEL). The National Institute for Occupational Safety and Health

(NIOSH,1992).

Time-Weighted Average (TWA). Occupational Safety and Health Administration (OSHA, 29

CFR 1910.1000, Table Z-1).

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Clear

Liquid

Amber.

Odour Mild, oily.

Flash point 224 'C

Vapour density >1

Bulk density 0,878 kg/l

Solubility(ies) Insoluble in water.

Auto-ignition temperature Not self-ignited Revision date: 22/08/2017 Revision: 2 Supersedes date: 16/03/2015

FULLGEAR FD 10W-30

Viscosity 56,2 mm2/sn (Viskozite 40'C)

Explosive properties Not considered to be explosive.

Oxidising properties Does not meet the criteria for classification as oxidising.

Comments Values are typical. These values may be variable within the product specification.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity None known.

10.2. Chemical stability

Stability Stable at normal ambient temperatures. Mixing with any other material.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Not relevant.

10.4. Conditions to avoid

Conditions to avoid Avoid freezing. Avoid contact with strong oxidising agents. Avoid exposure to high

temperatures or direct sunlight. Keep away from moisture.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Heating may generate the following products: Toxic and corrosive gases or vapours. Thermal decomposition or combustion products may include the following substances: Carbondioxide,carbon

monoxide, sulphur oxides, phosphorus oxides, metal oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No data recorded.

Other health effects No data available to indicate product or any components are

carcinogenic, mutagenic, genotoxic, and chronic health hazards.

General information Information given is based on a knowledge of the components and the toxicology of similar

products.

Inhalation Not expexted to cause irriation. Gas or vapour in high concentrations may irritate the

respiratory system. Symptoms following overexposure may include the following: Coughing.

Ingestion May cause discomfort if swallowed. The main symptoms are gastrointestinal ailments,

including upset stomach.

Skin contact Skin irritation should not occur when used as recommended. Repeated exposure may cause

skin dryness or cracking. May cause sensitisation or allergic reactions in sensitive individuals.

Eye contact Not expexted to cause eye irriation. Vapors formed from heating may cause eye irriation.

Revision date: 22/08/2017 Revision: 2 Supersedes date: 16/03/2015

FULLGEAR FD 10W-30

Acute and chronic health

hazards

The product contain special performance additives and mineral base oils which are considered to be severely refined and not considered to be carcinogenic. All of the base oils in the product have been demonstrated to contain less than 3% (w/w) dimethyl sulfoxide extract by the IP 346 test. USED ENGINE OILS are more dangerous than new engine oils. Used engine oils may contain hazardous components which have the potential to cause skin

cancer.

Route of entry Inhalation,ingestion,skin,eye contact.

Target organs Skin, eyes, respiratory system, lungs, gastro-intestinal tract.

SECTION 12: Ecological Information

EcotoxicityThe product contains/contain a substance/substrances which is harmful to aquatic organisms

and which may cause long term adverse effects in the aquatic environment.

12.1. Toxicity

Toxicity There is no specific test data available

12.2. Persistence and degradability

Persistence and degradability The product is not readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potentialThe product contains potentially bioaccumulating substances.

12.4. Mobility in soil

Mobility The product is insoluble in water and will spread on the water surface. It may absorbed by soil

and will not be mobile.

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Empty packages and wastes produced after the usage of the product should be taken under

control according to the current environmental regulations. Unless otherwise noted all wastes

should be evaluated as hazardous waste.

Disposal methods Disposal of this product, process solutions, residues and by-products

should at all times comply with the requirements of environmental protection and waste

disposal legislation and any local authority requirements.

Waste class 13 02 06*Synthetic engine, gear and lubricating oils

13 02 08*other engine, gear and lubricating oils

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

SECTION 16: Other information

General information All ingredients are listed in the European Inventories. However, they shall not constitute

aguarantee for any specific product features and shall not establish a legally validcontractual relationship. This data sheet is a safety data sheet according to 91/155/EU. For products which are not subject to classification according to EU lists this data sheet is made on a

voluntary base.

Key literature references and

sources for data

December 13, 2014, No. 29204, "the Ministry of Environment and the Ministry of Urban Development Related to Safety Data Sheets on Hazardous Substances and Mixtures

Direction"

Revision comments General revision.

Issued by AYŞEGÜL SÜER

MSc. R&D Engineer

Certified by NBC for MSDS (Certificate No: 01.42.05) Opet Fuchs Madeni Yağ Sanayi ve Ticaret A.Ş. AOSB Mustafa Kemal Bulvarı No:12 35620 Çiğli/İZMİR

E-Mail: Aysegul.SUER@opetfuchs.com.tr

Revision date 22/08/2017

Revision 2

Supersedes date 16/03/2015

SDS number OPET.GBF.0933

Hazard statements in full H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH208 Contains C14-18 alpha-olefin epoxide, reaction products with boric acid, Triphenyl

phosphite. May produce an allergic reaction.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information contained in this data sheet. OPET FUCHS MADENI YAG SAN. VE TIC. A.Ş. shall not be responsible for any injury or damage resulting from the abnormal use of the product, recipient assumes all such risks.