

technical data sheet

Fullmax FD 0W-20

High Performance in Fuel Economy







PRODUCT DESCRIPTION

Fullmax 0W-20, is a synthetic engine oil which meets the performance requirements of new technology engines. It is especially suitable to use Ford gasoline and diesel engines of passenger vehicles and light commercial vehicles

APPLICATIONS

• It is suitable to use in Ford vehicles which recommended WSS-M2C952-A1 specification.

CHARACTERISTICS

- It provides wear protection in new generation and high performance gasoline or diesel engines under all
 operating and driving conditions.
- It controls formation of deposit and sludge, so keeps the parts of engine clean and extends engine life.
- Its improved low viscosity property provides extreme fuel economy.
- Its superior thermal and oxidation stability maintains its performance during the long oil drain interval recommended by the engine manufacturers.

PERFORMANCES

Ford WSS-M2C952-A1

TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0,844
Viscosity@ 40°C, mm²/s	ASTM D 445	42,8
Viscosity@100°C, mm²/s	ASTM D 445	8,3
Viscosity Index	ASTM D 2270	174
Flash Point, °C	ASTM D 92	227
Pour Point, °C	ASTM D 5950	-45
TBN, mgKOH/g	ASTM D 2896	9,4







1/2

Phone: +90 216 522 69 00



technical data sheet

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers spesifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.

OPET.TDS.0116/Rev.00/22.04.2022



Phone: +90 216 522 69 00 **Fax** : +90 216 522 69 90

teknikservisler@opetfuchs.com.tr opetfuchs.com.tr