

### Fullpro HT SYN LD 5W-20

Ford Trucks New Generation Ecotorq Synthetic Engine Oil



#### PRODUCT DESCRIPTION

Fullpro HT SYN LD 5W-20, is an ultra high performance synthetic diesel engine oil which is specially developed for new generation low emission Euro VI engines of Ford Tow Trucks. Its special formula provides excellent wear protection, easy cold starting, low oil consumption and extended oil drain interval.

#### APPLICATIONS

- It is the first fill and service fill engine oil of new generation Ecotorq Euro VI engines of Ford Tow Trucks.
- It is suitable to use in Euro V and Euro VI diesel engines fitted with exhaust gas after treatment systems such as DPF, EGR, SCR.

#### CHARACTERISTICS

- It fulfills all performance needs of Ford ecotorq Euro VI engine. It is specially developed with the cooperation of Opet Fuchs and Ford Automotive engineers.
- New additive technology improves the efficiency of exhaust gas after treatment systems such as DPF (Diesel Particulate Filter), EGR (Exhaust Gas Recirculation) and SCR (Selective Catalytic Reduction) and prolongs the life of these systems.
- Its active cleaning feature offers residue and sludge control, so keeps engine parts clean.
- Its superior thermal and oxidation stability maintains its performance during the extended oil drain interval.
- It offers fuel economy.
- It provides excellent wear protection during cold start-up due to its improved low temperature characteristics.

#### PERFORMANCES

- FORD WSS-M2C219-A1

#### TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0,855
Viscosity@ 40°C, mm <sup>2</sup> /s	ASTM D 445	54,5
Viscosity@100°C, mm <sup>2</sup> /s	ASTM D 445	9,1
Viscosity Index	ASTM D 2270	148
Flash Point, °C	ASTM D 92	231
Pour Point, °C	ASTM D 97	-30
TBN, mgKOH/g	ASTM D 2896	11,3

### HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

*The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.*

*The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.*

*This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.*