

# SAFETY DATA SHEET **FULLPRO HT LSPS 10W-40**

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Product name FULLPRO HT LSPS 10W-40

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Engine Oil. Please look at the Technical Data Sheet of the product for further information.

#### 1.3. Details of the supplier of the safety data sheet

OPET FUCHS MADENI YAĞ SAN. ve TİC. A.Ş. Supplier

Atatürk Organize Sanayi Bölgesi 10006 Sok.

No:12 35620 Çiğli/İZMİR Tel: +90 232 376 78 38 Fax: +90 232 376 78 39

## 1.4. Emergency telephone number

**Emergency telephone** UZEM (National Poison Consultancy Center): 114

**Emergency Health Service:112** 

# **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified

Health hazards Not Classified

**Environmental hazards** Not Classified

Classification (67/548/EEC or NC not classified

1999/45/EC)

Human health No specific hazards under normal use conditions.

**Environmental** The product is not expected to be hazardous to the environment.

**Physicochemical** The product is not classified as flammable, but at a temperature above the flash point is

flammable when exposed to flame sources.

2.2. Label elements

Hazard statements NC Not Classified

#### 2.3. Other hazards

By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept.

## SECTION 3: Composition/information on ingredients

## 3.2. Mixtures

#### **FULLPRO HT LSPS 10W-40**

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-

60-80%

based;

Classification Classification (67/548/EEC or 1999/45/EC)

Asp. Tox. 1 - H304 Xn; R65

Distillates (petroleum), solvent-dewaxed heavy paraffinic

5-10%

CAS number: 64742-65-0 EC number: 265-169-7

Classification

Asp. Tox. 1 - H304

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

considered to be severely refined and not considered to be carcinogenic. All of the base oils in the product have been demonstrated to contain less than 3% (w/w) dimethyl sulfoxide extract

by the IP 346 test.

#### SECTION 4: First aid measures

## 4.1. Description of first aid measures

General information Change clothes and shoes contaminated or soaked by product. Never put rags contaminated

by product into cloth-pockets. Get medical attention if any discomfort continues. Not expected

to give rise to an acute hazard under normal conditions of use.

Inhalation Remove affected person from source of contamination and immediately take outside to fresh

air. Consult a doctor if any discomfort continues.

Ingestion IF SWALLOWED: Rinse mouth thoroughly with water. Get medical attention immediately. Do

not induce vomiting unless under the direction of medical personnel. Never give anything by mouth to an unconscious person. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Show this Safety Data Sheet to the medical personnel.

Skin contact Remove affected person from source of contamination. Remove contaminated clothing

immediately and wash skin with soap and water. Continue to rinse for at least 15 minutes. Brush off loose particles from skin. If adhesive bonding occurs, do not force skin apart. Get

medical attention.

Eye contact Do not rub eye. Remove any contact lenses and open eyelids wide apart. Rinse immediately

with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention if

symptoms are severe or persist after washing.

Protection of first aiders Wash contaminated clothing thoroughly with water before removing it from the affected

person, or wear gloves.

## 4.2. Most important symptoms and effects, both acute and delayed

InhalationNo specific symptoms known.IngestionNo specific symptoms known.Skin contactNo specific symptoms known.Eye contactNo specific symptoms known.

#### 4.3. Indication of any immediate medical attention and special treatment needed

## **FULLPRO HT LSPS 10W-40**

Notes for the doctor Symptomatic treatment should be applied. In case of excessive inhalation of the product

vapor may lead to lung inflammation (chemical pneumonitis). Dermatitis may result from

prolonged or repeated exposure.

**Specific treatments** Treat symptomatically.

## SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media Use Film-Making Foam Concentrate (A.F.F.F.) to extinguish the burning product. If not

available, extinguish with dry chemical powder due to the size of fire. If the product is in

pressurized container, cool with water spray jet.

Unsuitable extinguishing media

During a fire, DO NOT extinguish by applying pressurized water and water jet directly on the

burning product. Use water fog to cool down.

#### 5.2. Special hazards arising from the substance or mixture

Specific hazards This product is not explosive. Do not heat up near flash point.

Hazardous combustion products

In case of fire toxic and corrosive gases may form. These gases: Carbon dioxide, carbon

monoxide, sulphur oxides, phosporus oxides, metal oxides

## 5.3. Advice for firefighters

Protective actions during firefighting

In case of fire, shut off flow if it can be done without risk. Stop leak if safe to do so. Move undamaged containers from fire area if it can be done without risk. Prevent the burning product from entering into drainage system to avoid release of the product. To prevent spreading of the product build-up binders or barriers by using non-burning material such as sand. Use air-supplied respirators to protect against gases/fumes in case of fire-fighting.

Special protective equipment for firefighters

Fire-fighting should be done by trained personnel. Special protective full-clothing, air-supplied respirator, gloves and protective goggles should be worn. Dry chemical sand used for fire extinguishing and other fire extinguising equipment should meet the national and international standards.

#### SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions In case of spills, beware of

In case of spills, beware of slippery floors and surfaces. Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. For personal protection, see Section 8. Do not smoke, use open fire or other sources of ignition. Wear protective gloves and (in case of splashes) goggles/face shield too.

#### 6.2. Environmental precautions

**Environmental precautions** 

Avoid release to the environment. Avoid discharge into drains, water courses or onto the ground. To prevent release, place container with damaged side up. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to local appropriate regulatory body. Empty container contains product residue which may exhibit hazards of product.

## 6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Large Spillages: Stop leak if possible without risk. DO NOT touch spilled material! Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13. Avoid the spillage or runoff entering drains, sewers or watercourses. Inform authorities if large amounts are involved. Small Spillages: Stop leak if possible without risk. Dam and absorb spillage with sand,sawdust or other absorbent. Absorb in vermiculite, dry sand or earth and place into containers. Dispose of via an authorised person/licensed waste disposal contractor in accordance with local regulations.

### 6.4. Reference to other sections

## **FULLPRO HT LSPS 10W-40**

Reference to other sections

For handling and storage, see section 7. For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

#### SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

**Usage precautions** Provide adequate ventilation. Container must be kept tightly closed when not in use. Protect

against direct sunlight. Do not heat up the product near flash point. Avoid spilling,skin and eye contact. Avoid eating,dringking and smoking when using the product. Persons susceptible to

allergic reactions should not handle this product.

Advice on general occupational hygiene

Wash after use and before eating, smoking and using the toilet. Take off contaminated

clothing and wash it before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in a demarcated bunded area to prevent release to drains and/or watercourses. Store in

accordance with local regulations. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Protect from freezing and direct sunlight. Store in closed original container at temperatures between 0°C and 50°C. Keep away from food, drink and animal

feeding stuffs.

Storage class Not special storage precautions required.

7.3. Specific end use(s)

**Usage description** For containers or container linings, use mild steel or high density polyethylene (HDPE). For

containers or container linings, avoid PVC. Polyethylene containers should not be exposed to

high temperatures because of possible risk distortion.

## SECTION 8: Exposure Controls/personal protection

#### 8.1. Control parameters

Ingredient comments No exposure lin

No exposure limits known for ingredient(s).

## 8.2. Exposure controls

#### Protective equipment





Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. In case of insufficient ventilation, wear suitable respiratory equipment. Observe any occupational exposure limits for the product

or ingredients.

Personal protection In case of splashing or scattering, wear protective oil-resistant or chemical-resistant clothing.

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or

face shield.

## **FULLPRO HT LSPS 10W-40**

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended. Use thin cotton gloves inside the rubber gloves if allergy risk. The selection of suitable gloves does not only depend on the material, but also on further marks of quality varies from manufacturer. As the product is a pereparation of several substances, the resistance of the glove material can not be calculated in advance and has

therefore to be checked prior to the application.

Other skin and body

protection

Use skin protection cream for preventive skin protection. Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment

indicates skin contamination is possible.

**Hygiene measures** Provide eyewash station. Do not smoke in work area. Wash hands after contact. Promptly

remove non-impervious clothing that becomes contaminated. Contaminated clothing should be placed in a closed container for disposal or decontamination. Remove contaminated clothing and wash the skin thoroughly with soap and water after work. When using do not

eat, drink or smoke.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator

fitted with the following cartridge: High-efficiency particulate filter.

Thermal hazards Contact with hot product can cause serious thermal burns. If there is a risk of contact with hot

product, all protective equipment worn should be suitable for use with high temperatures.

Environmental exposure

controls

STEL: 10mg/m³ 15 minutes. Form: Oil mist, mineral TWA: 5mg/m³ 8 hours. Form: Oil mist, mineral

Short-Term Exposure Limit (STEL). The National Institute for Occupational Safety and Health

(NIOSH, 1992).

Time-Weighted Average (TWA). Occupational Safety and Health Administration (OSHA, 29

CFR 1910.1000, Table Z-1).

#### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

**Appearance** Clear

Liquid

ColourDark AmberOdourMild, oily.

Flash point 242°C COC (Cleveland open cup).

Bulk density 0,8607 kg/l @ 15°C

Solubility(ies) Insoluble in water.

Partition coefficient Not known.

Auto-ignition temperature Not self-ignited

**Viscosity** 99,54 mm<sup>2</sup>/s @ 40°C 14,65 mm<sup>2</sup>/s @ 100°C

**Explosive properties** Not considered to be explosive.

Oxidising properties Does not meet the criteria for classification as oxidising.

Comments Values are typical. These values may be variable within the product specification.

9.2. Other information

Other information No information required.

# **FULLPRO HT LSPS 10W-40**

## SECTION 10: Stability and reactivity

10.1. Reactivity

**Reactivity**No test data specifically related to reactivity available for this product or its ingredients.

10.2. Chemical stability

Stability Stable at normal ambient temperatures. Mixing with any other material.

10.3. Possibility of hazardous reactions

Possibility of hazardous

No potentially hazardous reactions known.

reactions

10.4. Conditions to avoid

Conditions to avoid Avoid freezing. Avoid contact with strong oxidising agents. Avoid exposure to high

temperatures or direct sunlight. Keep away from moisture.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Heating may generate the following products: Toxic and corrosive gases or vapours. Thermal decomposition or combustion products may include the following substances: Carbondioxide,carbon

monoxide, sulphur oxides, phosphorus oxides, metal oxides.

### SECTION 11: Toxicological information

# 11.1. Information on toxicological effects

**Toxicological effects** No data recorded.

Other health effects No data available to indicate product or any components are

carcinogenic, mutagenic, genotoxic, and chronic health hazards.

Skin corrosion/irritation

**Skin corrosion/irritation** No specific test data are available.

Serious eye damage/irritation

Serious eye damage/irritation No specific test data are available.

Respiratory sensitisation

**Respiratory sensitisation** No specific test data are available.

Skin sensitisation

**Skin sensitisation** No specific test data are available.

Germ cell mutagenicity

**Genotoxicity - in vitro**No specific test data are available.

Carcinogenicity

Carcinogenicity No specific test data are available.

Reproductive toxicity

**Reproductive toxicity - fertility** No specific test data are available.

Reproductive toxicity -

No specific test data are available.

development

Specific target organ toxicity - single exposure

## **FULLPRO HT LSPS 10W-40**

STOT - single exposure No specific test data are available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No specific test data are available.

Aspiration hazard

Aspiration hazard No specific test data are available

General information Information given is based on a knowledge of the components and the toxicology of similar

products.

Inhalation Not expexted to cause irriation. Gas or vapour in high concentrations may irritate the

respiratory system. Symptoms following overexposure may include the following: Coughing.

**Ingestion** May cause discomfort if swallowed. The main symptoms are gastrointestinal ailments,

including upset stomach.

Skin contact Skin irritation should not occur when used as recommended. Repeated exposure may cause

skin dryness or cracking. May cause sensitisation or allergic reactions in sensitive individuals.

Eye contact Not expexted to cause eye irriation. Vapors formed from heating may cause eye irriation.

Acute and chronic health

hazards

The product contain special performance additives and mineral base oils which are

considered to be severely refined and not considered to be carcinogenic. All of the base oils in the product have been demonstrated to contain less than 3% (w/w) dimethyl sulfoxide extract by the IP 346 test. USED OILS are more dangerous than new oils. Used oils may contain

hazardous components which have the potential to cause skin cancer.

Route of entry Inhalation,ingestion,skin,eye contact.

**Target organs** Skin,eyes,respiratory system,lungs,gastro-intestinal tract.

Medical symptoms This product contains para-dodecylphenol. Rats given high, repeated daily doses of para-

dodecylphenol by oral intubation experienced adverse reproductive effects. The relevance of

these effects to humans is uncertain.

Medical considerations

This product contains para-dodecylphenol. Pregnant rats given high, pepeated daily doses of

para-docecylphenol by oral intubation gave birth to pups with cleft palate and skeletal

malformations. The relevance of these effects to humans is uncertain.

#### **SECTION 12: Ecological Information**

**Ecotoxicity** No negative effects on the aquatic environment are known.

12.1. Toxicity

**Toxicity** There is no specific test data available

### 12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

## 12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not known.

12.4. Mobility in soil

Mobility The product is insoluble in water and will spread on the water surface. It may absorbed by soil

and will not be mobile.

## 12.5. Results of PBT and vPvB assessment

## **FULLPRO HT LSPS 10W-40**

Results of PBT and vPvB

assessment

There is no specific test data available.

12.6. Other adverse effects

Other adverse effects Not known.

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

General information Empty packages and wastes produced after the usage of the product should be taken under

control according to the current environmental regulations. Unless otherwise noted all wastes

should be evaluated as hazardous waste.

**Disposal methods** Disposal of this product, process solutions, residues and by-products

should at all times comply with the requirements of environmental protection and waste

disposal legislation and any local authority requirements.

Waste class 13 02 06\*Synthetic engine, gear and lubricating oils

13 02 08\*other engine, gear and lubricating oils

## SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

# 14.1. UN number

Not applicable.

# 14.2. UN proper shipping name

Not applicable.

#### 14.3. Transport hazard class(es)

No transport warning sign required.

## 14.4. Packing group

Not applicable.

#### 14.5. Environmental hazards

### Environmentally hazardous substance/marine pollutant

No.

# 14.6. Special precautions for user

Not applicable.

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

#### **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **FULLPRO HT LSPS 10W-40**

**EU legislation** Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18

December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Observe the general safety regulations when handling chemicals. The product is not subject to identification regulations under EC Directives until 2004/73/EC (31. ATP) and the Ordinance on Hazardous Materials. The concentrations of the dangerous compounds, which are possibly specified under point 3, are not above the value for classification. Local regulations

must be kept.

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

#### SECTION 16: Other information

General information All ingredients are listed in the European Inventories. However, they shall not constitute

aguarantee for any specific product features and shall not establish a legally validcontractual relationship. This data sheet is a safety data sheet according to 91/155/EU. For products which are not subject to classification according to EU lists this data sheet is made on a

voluntary base.

Key literature references and

sources for data

December 13, 2014, No. 29204, "the Ministry of Environment and the Ministry of Urban

Development Related to Safety Data Sheets on Hazardous Substances and Mixtures

Direction"

**Revision comments** Revised formulation.

Issued by AYŞEGÜL SÜER

MSc. R&D Engineer

Certified by NBC for MSDS (Certificate No: 01.42.05) Opet Fuchs Madeni Yağ Sanayi ve Ticaret A.Ş. AOSB 10006 Sok. No:12 35620 Çiğli/İZMİR E-Mail: Aysegul.SUER@opetfuchs.com.tr

Revision date 02/09/2016

Revision 5

Supersedes date 06/12/2010

SDS number OPET.GBF.0402

Risk phrases in full R65 Harmful: may cause lung damage if swallowed.

**Hazard statements in full** H304 May be fatal if swallowed and enters airways.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information contained in this data sheet. OPET FUCHS MADENI YAG SAN. VE TIC. A.Ş. shall not be responsible for any injury or damage resulting from the abnormal use of the product, recipient assumes all such risks.