

# **Arga B Series**

## General Purpose Automotive Grease Series

### **PRODUCT DESCRIPTION**

Arga B Series, is a superior performance lithium based greases for medium/high speed ball bearings and general automotive applications. It provides good protection against rust, corrosion and wear due to antirust and anti-wear (AW) additives, respectively.

#### **APPLICATIONS**

It is recommended for general automotive applications with an operating temperature between -20°C and 120°C.

#### **CHARACTERISTICS**

- Provides reliable performance in applications not requiring extreme pressure (EP).
- Easy pumping feature in cold weather conditions.
- Resists against rust, corrosion and wear.

#### **TYPICAL PROPERTIES**

NLGI Colour Soap Type DIN Classification ISO Classification Worked Penetration, 0.1 mm (25°C, 60 Stroke)	DIN 51502 ISO 6743-9 ASTM D 217	<b>2</b> Light Brown Lithium K 2 K-20 L-XBCEA-2 265-295	<b>3</b> Light Brown Lithium K 3 K-20 L-XBCEA-3 220-250
Base Oil Viscosity @40°C, mm <sup>2</sup> /s	ASTM D 445	100,0	100,0
Base Oil Viscosity @100°C, mm²/s	ASTM D 445	11,0	11,0
Dropping Point, °C,	ASTM D 566	>190	>190
Operating Temperature, °C		-20 to 120	-20 to 120
4-Ball Weld Load, N	ASTM D 2596	>2500	>2500

OPET.TDS.2200-1/Rev.08/10.07.2015

OPET FUCHS MADENİ YAĞ SANAYİ VE TİCARET A.S. Ord. Prof. Dr. Fahrettin Kerim Gökay Cad. Eşref Çakmak Plaza No: 32 Giriş Katı TR 34662 Altunizade/Üsküdar/İSTANBUL

Phone: +90 216 522 69 00 Fax : +90 216 522 69 90 teknikservisler@opetfuchs.com.tr opetfuchs.com.tr





#### HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers spesifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.



**OPET FUCHS MADENİ YAĞ SANAYİ VE TİCARET A.Ş.** Ord. Prof. Dr. Fahrettin Kerim Gökay Cad. Eşref Çakmak Plaza No: 32 Giriş Katı TR 34662 Altunizade/Üsküdar/İSTANBUL

2/2

OPET.TDS.2200-1/Rev.08/10.07.2015

Phone: +90 216 522 69 00 Fax : +90 216 522 69 90 teknikservisler@opetfuchs.com.tr opetfuchs.com.tr