

Arga Super EP 00

Semi-Fluid Extreme Pressure Automotive Grease

PRODUCT DESCRIPTION

Arga Super EP 00, is a semi-fluid lithium soap automotive grease that is used in roller bearings, and sliding bearings, central lubrication systems and applications operating under high loads up to 120°C.

APPLICATIONS

- It is suitable for roller and sliding bearings, central lubrication systems and applications operating under high loads up to 120°C.

CHARACTERISTICS

- Extreme pressure (EP) additives give an outstanding performance under high loads.
- Resists against water washout and provides longer re-greasing interval.
- Specially developed anti-wear and anti-corrosion additives provide superior rust, corrosion and wear protection.
- Easy pumping feature in cold weather conditions.

TYPICAL PROPERTIES

NLGI

Colour

Soap Type

DIN Classification

ISO Classification

Worked Penetration, 0,1mm
(25°C, 60 strokes)

Base Oil Viscosity @40°C, mm²/s

Base Oil Viscosity @100°C, mm²/s

Dropping Point, °C

Operating Temperature Range, °C

4-Ball Weld Load, N

DIN 51502

ISO 6743-9

ASTM D 217

ASTM D 445

ASTM D 445

ASTM D 566

ASTM D 2596

00

Light Brown

Lithium

KP 00 K-30

L-XCCEB-00

400-430

220,0

19,0

>170

-30 to 120

2400

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.