

## ATF CVT

# Synthetic Continuously Variable Transmission (CVT) Fluid

### PRODUCT DESCRIPTION

**ATF CVT**, is a synthetic automatic transmission fluid based on special technology base oils and additives. It is specialy formulated for continuously variable transmission of passenger cars.

### **APPLICATIONS**

• It is suitable to use continuous variable transmission (CVT) of passenger cars.

#### **CHARACTERISTICS**

- Provides effective wear protection even at very low temperatures and under high load, so extends the lifetime of the automatic transmission and lowers maintanence costs.
- Minimizes friction and dissipates heat, so provides smooth gear shifting over a wide operating temperature range.
- Outstanding oxidation and shear stability offers relaible peroformance during long drain interval.
- Excellent performance in cold and very high temperature operation.

#### **PERFORMANCES**

- CHRYSLER NS-2 / CVTF+4
- CVT FLUID J1
- CVT FLUID DFE
- DAIHATSU AMMIX CVT FLUID DC
- FORD CVT23
- HONDA HCF-2
- MAZDA CVTF 3320

- MINI COOPER EXL799
- MMC DIAQUEES ATF SP-III
- NISSAN CVT FLUID NS-1 / NS-2 / NS-3
- SUBARU I-CVT / I-CVT FG
- SUZUKI CVT FLUID 3320
- SUZUKI CVT FLUID GREEN 1 / 2
- TOYOTA CVT FLUID TC / TE

#### TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0,847
Viscosity@ 40°C, mm²/s	ASTM D 445	31,9
Viscosity@100°C, mm²/s	ASTM D 445	6,9
Viscosity Index	ASTM D 2270	185
Flash Point, °C	ASTM D 92	204
Pour Point, °C	ASTM D 97	-51

OPET.TDS. 0939/Rev.00/21.02.2019



1/2

Phone: +90 216 522 69 00



#### HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers spesifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.



OPET.TDS. 0939/Rev.00/21.02.2019

Phone: +90 216 522 69 00

opetfuchs.com.tr