

### ATF DX VI

## High Performance Automatic Transmission Fluid



### PRODUCT DESCRIPTION

ATF DX VI, is a low viscosity, high performace synthetic transmission fluid that meets GM Dexron VI, Ford Mercon LV and JASO 1-A LV specifications.

### **APPLICATIONS**

- It is used in automatic transmissions and power steering systems of passenger cars and commercial vehicles where GM Dexron VI, Ford Mercon LV and JASO 1-A LV are required.
- It is also suitable for use in hydraulic power systems where an automatic transmission fluid is specified.

#### **CHARACTERISTICS**

- Low viscosity formula provides fuel efficiency
- It reduces maintenance costs and exdends automatic transmission's life at low temperatures and under extreme road conditions while providing excellent protection against wear
- Reduces friction and heat, so provides smooth gear shift over wide operating temperature range.
- Superior oxidation stability and shear stability.

#### **PERFORMANCES**

- FORD MERCON LV
- **GM DEXRON VI**
- JASO 1-A LV

#### TYPICAL PROPERTIES

Colour		Red
Density@15°C, g/ml	ASTM D 4052	0,841
Viscosity@ 40°C, mm²/s	ASTM D 445	28,6
Viscosity@100°C, mm²/s	ASTM D 445	5,9
Viscosity Index	ASTM D 2270	162
Flash Point, °C	ASTM D 92	212
Pour Point, °C	ASTM D 97	-42

OPET.TDS. 0941/Rev.00/19.04.2019



1/2

opetfuchs.com.tr



# technical data sheet

#### **HEALTH AND SAFETY RECOMMENDATIONS**

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers spesifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.



OPET.TDS. 0941/Rev.00/19.04.2019

2/2

Phone: +90 216 522 69 00