

ATF MV

Automatic Transmission Fluid

PRODUCT DESCRIPTION

ATF MV, is an automatic transmission fluid based on special technology additives. It is developed to meet JASO 1-A specification of Japanese Automobile Standards Organisation.

CHARACTERISTICS

- Outstanding oxidation and shear stability offers reliable performance during long drain interval
- Provides effective wear protection even at very low temperatures and under high load, so extends the lifetime of the automatic transmission and lowers maintenance costs.

APPLICATIONS

- It is suitable for use in Japanese passenger cars which recommended JASO 1-A specification.

PERFORMANCES

- Audi G 052 162, G052 990, G055 025
- BMW 7045E, 8072B, LA 2634, LT 71141
- Honda ATF Z-1
- Hyundai/Kia SP-II, SP-III, JWS 3314, JWS 3317, JWS 3309
- Idemitsu K17
- JASO 1-A
- Kia Red-1
- Mazda ATF –M III, ATF-MV
- Mercedes-Benz MB 236.1, 236.2, 236.3, 236.5, 236.6, 236.7, 236.9, 236.10
- Mitsubishi SP-II, SP-III, Diaqueen ATF J2
- Nissan 402, Nissan Matic-D, J, K
- PSA AL-4
- Renault DP-0
- Subaru ATF, ATF-HP
- Suzuki 3314, 3317
- Toyota T, T-II, T-III, T-IV
- Volvo 4 speed (P/N 1161621)
- Volvo 5/6 speed (P/N 1161540/1161640)
- VW G 052162, G 052 990, G 055 025
- ZF TE-ML 11

TYPICAL PROPERTIES

Colour	ASTM D 1500	2.0
Appearance	TM 07-1	Clear
Density@15°C, g/ml	ASTM D 4052	0,853
Viscosity@ 40°C, mm²/s	ASTM D 445	43,3
Viscosity@100°C, mm²/s	ASTM D 445	7,9
Viscosity Index	ASTM D 2270	156
Flash Point, °C	ASTM D 92	216
Pour Point, °C	ASTM D 97	-42

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.