

ATF MV

Automatic Transmission Fluid

PRODUCT DESCRIPTION

ATF MV, is an automatic transmission fluid based on special technology additives. It is developed to meet JASO 1-A specification of Japanese Automobile Standards Organisation.

APPLICATIONS

- It is suitable for use in Japanese passenger cars which recommended JASO 1-A specification.

CHARACTERISTICS

- Outstanding oxidation and shear stability offers reliable performance during long drain interval
- Provides effective wear protection even at very low temperatures and under high load, so extends the lifetime of the automatic transmission and lowers maintenance costs.

PERFORMANCES

- BMW ETL-7045, ETL-7045 E, ETL-8072 B, LA 2634
- GM 6032M(D), GM 6137M(E), GM 6417M(G), GM N10055(H)
- HONDA ATF Z-1
- HYUNDAI/KIA SP-III
- HYUNDAI ATF RED-1K
- ISUZU GENUINE ATF
- JAGUAR K17
- JASO 1-A
- LAND ROVER N402
- MB-APPROVAL 236.1, 236.6, 236.7, 236.8 236.9, 236.10
- MITSUBISHI SP-III, ATF ATF-J2
- MOPAR ASRC
- NISSAN FLUID A, NISSAN MATIC-D, J, K
- SAAB TRANSMAX J, ATF Z1
- SUBARU ATF
- SUZUKI MATIC J, MATIC D ATF
- TOYOTA TYPE T, JWS 3324, JWS 3309
- VW G 052 025, VW GUS 00 162

TYPICAL PROPERTIES

Colour	ASTM D 1500	Red
Appearance	TM 07-1	Clear
Density@15°C, g/ml	ASTM D 4052	0,850
Viscosity@ 40°C, mm ² /s	ASTM D 445	35,1
Viscosity@100°C, mm ² /s	ASTM D 445	6,7
Viscosity Index	ASTM D 2270	151
Flash Point, °C	ASTM D 92	224
Pour Point, °C	ASTM D 5950	-45

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.