

ATF XO

Super High Performance Synthetic Automatic



Transmission Fluid

PRODUCT DESCRIPTION

ATF XO, is a synthetic automatic transmission fluid based on special technology base oils and additives. It is specialy formulated for new generation automatic transmissions of passenger cars, light commercial and heavy duty vehicles. ATF XO achieves maximum drain intervals and provides smooth gear shifting.

APPLICATIONS

It is recommend for use in new generation automatic transmissions passenger cars, light commercial and heavy duty vehicles.

CHARACTERISTICS

- Provides effective wear protection even at very low temperatures and under high load, so extends the lifetime of the automatic transmission and lowers maintanence costs
- Minimizes friction and dissipates heat, so provides smooth gear shifting over a wide operating temperature range.
- Outstanding oxidation and shear stability offers relaible peroformance during long drain interval.
- Excellent performance in cold and very high temperature operation.

APPROVALS

VOITH H55.6336.xx

PERFORMANCES

- **ALLISON C-4**
- **ALLISON TES-295**
- FORD MERCON
- GM DEXRON III-H

TYPICAL PROPERTIES

Density@15°C, g/ml Viscosity@ 40°C, mm²/s Viscosity@100°C, mm²/s Viscosity Index Flash Point, °C Pour Point, °C

- MAN 339 TYPE V2/Z2/Z11
- MB-APPROVAL 236.9
- VOLVO 97341

0,847

31,9

6,9

185 204

-51

ZF TE-ML 20B / 14B / 03D

ASTM D 4052

ASTM D 445

ASTM D 445

ASTM D 92

ASTM D 97

ASTM D 2270

OPET.TDS. 0934/Rev.05/05.04.2019

s Koc

OPET FUCHS MADENİ YAĞ SANAYİ VE TİCARET A.Ş. Ord. Prof. Dr. Fahrettin Kerim Gökay Cad. Eşref Çakmak Plaza No: 32 Giriş Katı TR 34662 Altunizade/Üsküdar/İSTANBUL

Phone: +90 216 522 69 00 Fax :+90 216 522 69 90 teknikservisler@opetfuchs.com.tr opetfuchs.com.tr



HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers spesifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.



2/2

OPET.TDS. 0934/Rev.05/05.04.2019

Phone: +90 216 522 69 00 Fax : +90 216 522 69 90 teknikservisler@opetfuchs.com.tr opetfuchs.com.tr