

Fullgear FD 10W-30

Multi Purpose Transmission Oil for Construction Machines

PRODUCT DESCRIPTION

Fullgear FD 10W-30, is a multi purpose transmission oil for manual or automatic transmissions, hydraulic, axle, wet brake systems, final drives and PTO (Power take Off) of construction machines. Quality base oils and antifriction additives in its formulation provide high performance while power transmission in moving components.

CHARACTERISTICS

- It provides effective protection against high velocity/low torque and low velocity/high torque wear.
- Its high viscosity-temperature behaviour enables effective performance even at low temperatures.
- Its anti-friction additives allow wet brake system operates efficiently and silently.
- Its specially developed formula provides long service life by controllig rust, corrosion and foam formation.
- Its high thermal and oxidation stability prevents sludge formation and increases operating efficiency.

APPLICATIONS

It is suitable to use in manuael or automatic transmissions, hydraulic, axle, wet brake systems and PTO of construction machines.

PERFORMANCES

- ALLISON C-4
- API GL-4
- CAT TO-2
- CNH MAT3525/3505
- **VCE WB 101**
- ZF TE-ML 21F/17E/06K/05F/03E



OPET FUCHS MADENI YAĞ SANAYI VE TİCARET A.Ş. Phone: +90 216 522 69 00 Ord. Prof. Dr. Fahrettin Kerim Gökay Cad. Eşref Çakmak Plaza No: 32 Giriş Katı TR 34662 Altunizade/Üsküdar/İSTANBUL

1/2

OPET.TDS.0926/Rev.08/05.02.2018

Fax : +90 216 522 69 90 teknikservisler@opetfuchs.com.tr opetfuchs.com.tr



TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0,878
Viscosity@ 40°C, mm²/s	ASTM D 445	58,6
Viscosity@100°C, mm²/s	ASTM D 445	9,7
Viscosity Index	ASTM D 2270	152
Flash Point, °C	ASTM D 92	224
Pour Point, °C	ASTM D 97	-36

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers spesifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.

2/2

M Koc

OPET FUCHS MADENI YAĞ SANAYI VE TİCARET A.Ş. Phone: +90 216 522 69 00 Ord. Prof. Dr. Fahrettin Kerim Gökay Cad. Eşref Çakmak Plaza No: 32 Giriş Katı TR 34662 Altunizade/Üsküdar/İSTANBUL

OPET.TDS.0926/Rev.08/05.02.2018

Fax :+90 216 522 69 90 teknikservisler@opetfuchs.com.tr opetfuchs.com.tr