

Fulllife S 10W-40

Synthetic Based Optimum Lubrication

PRODUCT DESCRIPTION

Fulllife S 10W-40, is a synthetic based engine oil which is formulated with unique combination of oils quality base and advanced additive technology to meet the lubrication needs of gasoline or diesel engines.

CHARACTERISTICS

- It keeps engine parts clean and extends engine life by controling deposit and sludge formation.
- It maintains its lubrication until the next oil change due to its high oxidation stability.
- Its maintains its protection even under extreme operating conditions due to its durable oil film strength.
- Its high viscosity index provides superior performance under variable weather conditions.

APPLICATIONS

It is suitable to use in gasoline or diesel engines of passenger cars and light commercial vehicles where viscosity and performance requirements is appropriate.

PERFORMANCES

API SN/SM/CF

OPET.TDS.0200/Rev.13/20.02.2019

OPET FUCHS MADENİ YAĞ SANAYİ VE TİCARET A.Ş. Ord. Prof. Dr. Fahrettin Kerim Gökay Cad. Eşref Çakmak Plaza No: 32 Giriş Katı TR 34662 Altunizade/Üsküdar/İSTANBUL

1/2

Phone: +90 216 522 69 00 Fax :+90 216 522 69 90 teknikservisler@opetfuchs.com.tr opetfuchs.com.tr

s Koc



TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0,875
Viscosity@ 40°C, mm²/s	ASTM D 445	91,69
Viscosity@100°C, mm²/s	ASTM D 445	13,54
Viscosity Index	ASTM D 2270	149
Flash Point, °C	ASTM D 92	232
Pour Point, °C	ASTM D 97	-39
TBN, mgKOH/g	ASTM D 2896	11,6

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers spesifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yag. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.

2/2

OPET.TDS.0200/Rev.13/20.02.2019

OPET FUCHS MADENI YAĞ SANAYİ VE TİCARET A.Ş. Phone: +90 216 522 69 00 Ord. Prof. Dr. Fahrettin Kerim Gökay Cad. Eşref Çakmak Plaza No: 32 Giriş Katı TR 34662 Altunizade/Üsküdar/İSTANBUL

Fax : +90 216 522 69 90 teknikservisler@opetfuchs.com.tr opetfuchs.com.tr

