

technical data sheet

Fulllife 15W-40

Optimum Lubrication for High Mileage Vehicles



PRODUCT DESCRIPTION

Fulllife 15W-40, is an engine oil which meets the lubrication requirements of gasoline or diesel engines of passenger vehicles and light commercial vehicles. Also, it is ideal for high mileage vehicles.

APPLICATIONS

• It is suitable to use in gasoline or diesel engines of passenger vehicles and light commercial vehicles.

CHARACTERISTICS

- Its active cleaning feature controls forming of deposit and sludge, so keeps the engine parts clean.
- Its maintains its lubrication even under extreme operating conditions due to its durable oil film strength.
- Its high oxidation stability maintains its protection until the next oil change.
- It provides superior protection especially in high mileage vehicles.
- Its high viscosity index provides engine to function properly.

PERFORMANCES

API SL/CF

TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0,883
Viscosity@ 40°C, mm²/s	ASTM D 445	99,7
Viscosity@100°C, mm²/s	ASTM D 445	13,3
Viscosity Index	ASTM D 2270	132
Flash Point, °C	ASTM D 92	239
Pour Point, °C	ASTM D 97	-36
TBN, mgKOH/g	ASTM D 2896	7,8

OPET FUCHS MADENİ YAĞ SANAYİ VE TİCARET A.Ş. Ord. Prof. Dr. Fahrettin Kerim Gökay Cad. Eşref Çakmak Plaza No: 32 Giriş Katı TR 34662 Altunizade/Üsküdar/İSTANBUL



 Phone:
 +90 216 522 69 00

 Fax
 :
 +90 216 522 69 90

 teknikservisler@opetfuchs.com.tr
 opetfuchs.com.tr

1/2



HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers spesifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.

OPET.TDS.0202/Rev.08/12.03.2019

Moc

OPET FUCHS MADENİ YAĞ SANAYİ VE TİCARET A.Ş. Ord. Prof. Dr. Fahrettin Kerim Gökay Cad. Eşref Çakmak Plaza No: 32 Giriş Katı TR 34662 Altunizade/Üsküdar/İSTANBUL

Phone: +90 216 522 69 00 Fax : +90 216 522 69 90 teknikservisler@opetfuchs.com.tr opetfuchs.com.tr

2/2