

## Fulllife 5W-30

# Optimum Lubrication with Synthetic Technology

### PRODUCT DESCRIPTION

Fulllife 5W-30, is a synthetic based engine oil meet developed to high performance requirements of passenger cars light commercial vehicles. It is developed with special anti-wear additives minimize engine wear.

#### **CHARACTERISTICS**

- Its high oxidation stability maintains its protection until the next oil change.
- Its high viscosity index provides superior engine performance for all-season.
- Its excellent fluidity during cold weather conditions provides fast lubrication of engine parts during first start up, so protects the engine against wear.
- It reduces oil consumption due to Its low volatility; so helps the decrease of hydrocarbon pollution.

### **APPLICATIONS**

- It is suitable to use in gasoline or diesel engines of passenger vehicles and light commerical vehicles.
- It is suitable to use in Japanese vehicles which recommended ILSAC GF-5 specification.

#### **PERFORMANCES**

- API SN
- ILSAC GF-5

OPET.TDS. 0206/Rev.01/28.03.2019



1/2

Phone: +90 216 522 69 00



#### TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0,852
Viscosity@ 40°C, mm²/s	ASTM D 445	59,6
Viscosity@100°C, mm²/s	ASTM D 445	10,7
Viscosity Index	ASTM D 2270	173
Flash Point, °C	ASTM D 92	228
Pour Point, °C	ASTM D 97	-45
TBN, mgKOH/g	ASTM D 2896	8,23

#### **HEALTH AND SAFETY RECOMMENDATIONS**

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers spesifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.

OPET.TDS. 0206/Rev.01/28.03.2019



2/2