

technical data sheet

Fulllife LPG 20W-50

Optimum Lubrication for LPG Engines



PRODUCT DESCRIPTION

Fullife LPG 20W-50, is an engine oil which is formulated with advanced additive technology to meet the lubrication needs of passenger vehicles or light commercial vehicles with LPG engines. It is developed with special anti-wear additives to minimize engine wear.

APPLICATIONS

It is suitable to use in passenger vehicles or light commerical vehicles with LPG engines.

CHARACTERISTICS

- Its high oxidation stability maintains its protection until the next oil change.
- Its special additives protects engine against corrosion and wear.
- Its active cleaning fetaure controls forming of deposit and sludge, so keeps the engine parts clean.
- Its high viscosity index provides engine to function properly.

PERFORMANCES

M Koc

API SL/CF

TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0,898
Viscosity@ 40°C, mm²/s	ASTM D 445	144,2
Viscosity@100°C, mm²/s	ASTM D 445	16,9
Viscosity Index	ASTM D 2270	126
Flash Point, °C	ASTM D 92	256
Pour Point, °C	ASTM D 97	-30
TBN, mgKOH/gr	ASTM D 2896	8,0

1/2

OPET.TDS.0205/Rev.08/25.02.2019

OPET FUCHS MADENI YAĞ SANAYİ VE TİCARET A.Ş. Phone: +90 216 522 69 00 Ord. Prof. Dr. Fahrettin Kerim Gökay Cad. Esref Çakmak Plaza No: 32 Giriş Katı TR 34662 Altunizade/Üsküdar/İSTANBUL

Fax :+90 216 522 69 90 teknikservisler@opetfuchs.com.tr opetfuchs.com.tr



HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers spesifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.

OPET.TDS.0205/Rev.08/25.02.2019

OPET FUCHS MADENI YAĞ SANAYI VE TİCARET A.S. Phone: +90 216 522 69 00 Ord. Prof. Dr. Fahrettin Kerim Gökay Cad. Esref Çakmak Plaza No: 32 Giriş Katı TR 34662 Altunizade/Üsküdar/İSTANBUL

2/2

Fax : +90 216 522 69 90 teknikservisler@opetfuchs.com.tr opetfuchs.com.tr

