



Fullmaster 15W-40

Effective Protection for High Mileage Heavy



Duty Vehicles

PRODUCT DESCRIPTION

Fullmaster 15W-40, is a diesel engine oil that is developed with combination of modern technology additives and high quality base oils. It completely fullfil the lubrication requirements of naturally aspirated or turbocharged diesel engines of heavy duty vehicles. Its special formula keeps engine parts clean and provides effective protection especially in frequently used and high mileage diesel engines.

APPLICATIONS

 It can be used in normally aspirated and turbocharged engines of heavy duty vehicles during all season and road conditions.

CHARACTERISTICS

- It protects engine parts against wear during start up.
- It keeps engine parts clean and extends service life.
- It reduces maintanence cost by providing effective protection in high mileage engines.

PERFORMANCES

s Koc

API CF-4

TYPICAL PROPERTIES

ASTM D 4052	0,887
ASTM D 445	107,6
ASTM D 445	14,2
ASTM D 2270	133
ASTM D 92	220
ASTM D 97	-27
ASTM D 2896	11,5
	ASTM D 445 ASTM D 445 ASTM D 2270 ASTM D 92 ASTM D 97

OPET.TDS.0510/Rev.01/16.09.2020

OPET FUCHS MADENİ YAĞ SANAYİ VE TİCARET A.Ş. Ord. Prof. Dr. Fahrettin Kerim Gökay Cad. Eşref Çakmak Plaza No: 32 Giriş Katı TR 34662 Altunizade/Üsküdar/İSTANBUL

Phone: +90 216 522 69 00 Fax : +90 216 522 69 90 teknikservisler@opetfuchs.com.tr opetfuchs.com.tr



HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers spesifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.



OPET FUCHS MADENİ YAĞ SANAYİ VE TİCARET A.Ş. Ord. Prof. Dr. Fahrettin Kerim Gökay Cad. Eşref Çakmak Plaza No: 32 Giriş Katı TR 34662 Altunizade/Üsküdar/İSTANBUL

2/2

OPET.TDS.0510/Rev.01/16.09.2020

Phone: +90 216 522 69 00 Fax : +90 216 522 69 90 teknikservisler@opetfuchs.com.tr opetfuchs.com.tr