

Fullmaster Turbo 15W-40

Effective Protection Against Engine Wear

PRODUCT DESCRIPTION

Fullmaster Turbo 15W-40, is a diesel engine oil that is specially formulated with modern technology additives and high quality base oils. It completely fullfil the lubrication requirements of naturally aspirated or turbocharged diesel engines of light and heavy commercial vehicles, agricultural and construction equipments. It provides effective protection in high mileage vehicles.

APPLICATIONS

It is suitable to use in naturally aspirated or turbocharged diesel engines of light and heavy commercial vehicles, agricultural and construction equipments.

CHARACTERISTICS

- It protects engine parts against wear during start up.
- It keeps engine parts clean and extends service life.
- It reduces soot and deposit formation.

PERFORMANCES

- ACEA E7
- API CH-4
- CUMMINS 20076 / 77
- MACK EO-M PLUS, EO-N
- MAN 3275
- MB-APPROVAL 228.3
- MTU TYPE 2
- **RENAULT RLD-2**
- VOLVO VDS-3

TYPICAL PROPERTIES

ASTM D 4052	0,886
ASTM D 445	100,6
ASTM D 445	13,7
ASTM D 2270	137
ASTM D 92	222
ASTM D 5950	-36
ASTM D 2896	12,0
	ASTM D 445 ASTM D 445 ASTM D 2270 ASTM D 92 ASTM D 5950



OPET FUCHS MADENİ YAĞ SANAYİ VE TİCARET A.S. Phone: +90 216 522 69 00 Ord. Prof. Dr. Fahrettin Kerim Gökay Cad. Esref Cakmak Plaza

No: 32 Giris Katı TR 34662 Altunizade/Üsküdar/İSTANBUL

1/2

OPET.TDS.0505/Rev.12/12.02.2020

Fax : +90 216 522 69 90 teknikservisler@opetfuchs.com.tr opetfuchs.com.tr



HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers spesifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.



OPET FUCHS MADENİ YAĞ SANAYİ VE TİCARET A.Ş. Ord. Prof. Dr. Fahrettin Kerim Gökay Cad. Eşref Çakmak Plaza No: 32 Giriş Katı TR 34662 Altunizade/Üsküdar/İSTANBUL

2/2

OPET.TDS.0505/Rev.12/12.02.2020

Phone: +90 216 522 69 00 Fax : +90 216 522 69 90 teknikservisler@opetfuchs.com.tr opetfuchs.com.tr