

Fullmax 10W-30

Synthetic Based Maximum Protection





PRODUCT DESCRIPTION

Fullmax 10W-30, is a synthetic based engine oil that meets the highest performance needs of gasoline and diesel engines. It provides an effective protection even if it is used with high sulphur fuels. It is formulated with specially selected base oils and new technology additives.

APPLICATIONS

• It is suitable to use in gasoline and diesel engines of leading vehicle manufacturers, especially Ford.

CHARACTERISTICS

- Its excellent fluidity during cold weather conditions protects the engine against wear by providing quick lubrication of engine parts during the first start.
- It provides fuel economy due to its special formula.
- Its active cleaning feature controls deposit and sludge formation, so keeps the engine parts clean.
- Its improved high and low temperature properties protects engine parts in all weather and driving conditions.
- Its superior thermal and oxidation stability preserves its performance during the oil drain interval recommended by the engine manufacturers.

PERFORMANCES

- ACEA E7
- API CI-4/CH-4/CG-4/CF-4/CF
- API SL
- FORD WSS-M2C921-A
- MACK EO-N
- MTU TYPE 2
- RENAULT RLD-2
- VOLVO VDS-3

TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0,874
Viscosity@ 40°C, mm²/s	ASTM D 445	77,6
Viscosity@100°C, mm²/s	ASTM D 445	11,9
Viscosity Index	ASTM D 2270	148
Flash Point, °C	ASTM D 92	221
Pour Point, °C	ASTM D 5950	-39
TBN, mgKOH/g	ASTM D 2896	11,2

1/2



teknikservisler@opetfuchs.com.tr opetfuchs.com.tr

OPET.TDS.0103/Rev.11/22.09.2020





technical data sheet

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with used oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers spesifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.



Phone: +90 216 522 69 00
Fax : +90 216 522 69 90

teknikservisler@opetfuchs.com.tr opetfuchs.com.tr