

Fullmax TF-D 0W-30

Maximum Protection For Euro 6 Diesel Engines

PRODUCT DESCRIPTION

Fullmax TF-D 0W-30, is a synthetic engine oil that meets the Euro 6 emission standards of diesel engines of passenger cars and commercial vhicles. It is specially developed for FIAT low emission diesel engines. Its special formula provides good cold starting, lower oil consumption, minimized exhaust emmisions and fuel economy.

APPLICATIONS

- It is especially recommended for low emission diesel engine FIAT vehicles which requires FIAT 9.55535-DS1 performance.
- It is suitable to use in passenger vehicles or light commercial vehicles where viscosity and performance level requirements are appropriate

CHARACTERISTICS

- Its special formula enables exhaust gas after treatment systems such as DPF and TWC to operate efficiently and extends service life of these systems.
- Its active cleaning feature controls the deposit and sludge formation, thus keeps the engine parts clean and decreases maintanence cost.
- Its improved friction property provides fuel economy.
- Its superior thermal and oxidation stability maintains its performance during the long oil drain interval that is recommended by the engine manufacturers.
- Its excellent fluidity during cold weather conditions provides quick lubrication of engine parts during first start up, thus protects the engine against wear.

PERFORMANCES

- ACEA C2
- FIAT 9.55535-DS1

TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0,845
Viscosity@ 40°C, mm²/s	ASTM D 445	49,2
Viscosity@100°C, mm²/s	ASTM D 445	9,4
Viscosity Index	ASTM D 2270	178
Flash Point, °C	ASTM D 92	220
Pour Point, °C	ASTM D 97	-39
TBN, mgKOH/g	ASTM D 2867	7,5

1/2

OPET.TDS.0111/Rev.01/9.3.2018





technical data sheet

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers spesifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.



OPET.TDS.0111/Rev.01/9.3.2018

2/2

opetfuchs.com.tr