

### Fullmono HD Plus 50

#### Monograde Engine Oil

#### PRODUCT DESCRIPTION

Fullmono HD Plus 50, is a high performance monograde engine oil which is formulated with quality base oils and special additives.

#### APPLICATIONS

- It is suitable to use in naturally aspirated poor performance diesel and gasoline engines.

#### CHARACTERISTICS

- Its detergent and dispersant additives keeps the engine clean and extends the life of engine parts.
- Its high thermal stability reduces formation of soot and deposit.

#### PERFORMANCES

- API CD/SE

#### TYPICAL PROPERTIES

SAE		50
Density@15°C, g/ml	ASTM D 4052	0,893
Viscosity@ 40°C, mm <sup>2</sup> /s	ASTM D 445	221,7
Viscosity@100°C, mm <sup>2</sup> /s	ASTM D 445	19,1
Viscosity Index	ASTM D 2270	97
Flash Point, °C	ASTM D 92	270
Pour Point, °C	ASTM D 97	-12

### HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

*The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.*

*The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.*

*This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.*