

Fullmono XH Series

Extra Performance Monograde Engine Oil

PRODUCT DESCRIPTION

Fullmono XH Series, is a super high performance monograde engine oil which is formulated with quality base oils and special additives. It is suitable to use in intercooler, turbocharged or naturally aspirated diesel engines under extreme operating conditions.

CHARACTERISTICS

- Its high thermal and oxidation stability prevents formation of deposit and sludge, so keeps engine clean.
- It has high TBN stability controls formation of acid, so reduces wear and extends oil drain interval.

TYPICAL PROPERTIES

SAE		10W	30
Density@15°C, g/ml	ASTM D 4052	0,882	0,890
Viscosity@ 40°C, mm ² /s	ASTM D 445	43,0	101,0
Viscosity@100°C, mm ² /s	ASTM D 445	6,5	11,5
Viscosity Index	ASTM D 2270	100	95
Flash Point, °C	ASTM D 92	230	238
Pour Point, °C	ASTM D 97	-30	-21
TBN, mgKOH/g	ASTM D 2896	7.0	7,0

APPLICATIONS

- It is suitable to in intercooler, turbocharged or naturally aspirated diesel engine under extreme operating conditions.
- **Fullmono XH 10W**, can be used in hydraulic systems of construction equipments if it recommended by the manufacturers.

PERFORMANCES

- API CF/SF

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.