

Fullmoto 4T SCT 20W-40

Ultra High Performance for Your Motorcycle

PRODUCT DESCRIPTION

Fullmoto 4T SCT 20W-40 is a motorcycle oil for air or water cooled four-stroke engines. It is specially developed with quality base oils and advanced technology additives.

APPLICATIONS

- It is suitable to use in air or water cooled 4-stroke engines where viscosity and performance level requirements are appropriate.
- It is recommended for Japanese and European manufactured modern motorcyles requiring API SG and JASO MA performance.

CHARACTERISTICS

- It provides high motorcycle performance especially under heavy traffic and urban riding conditions.
- It provides excellent wear protection during first start up.
- Its specially developed formula enables easy and smooth shifting.
- It offers good corrosion resistance and keeps engine and other parts clean even in intermittent use.

PERFORMANCES

- API SG
- JASO MA

TYPICAL PROPERTIES

ASTM D 4052	0,886
ASTM D 445	119,2
ASTM D 445	14,6
ASTM D 2270	124
ASTM D 92	245
ASTM D 97	-21
	ASTM D 445 ASTM D 445 ASTM D 2270 ASTM D 92

OPET.TDS.0705/Rev.03/16.04.2019

s Koc

OPET FUCHS MADENI YAĞ SANAYI VE TİCARET A.Ş. Phone: +90 216 522 69 00 Ord. Prof. Dr. Fahrettin Kerim Gökay Cad. Eşref Çakmak Plaza No: 32 Giriş Katı TR 34662 Altunizade/Üsküdar/İSTANBUL

Fax : +90 216 522 69 90 teknikservisler@opetfuchs.com.tr opetfuchs.com.tr



technical data sheet

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers spesifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.



OPET FUCHS MADENI YAĞ SANAYI VE TİCARET A.Ş. Phone: +90 216 522 69 00 Ord. Prof. Dr. Fahrettin Kerim Gökay Cad. Eşref Çakmak Plaza No: 32 Giriş Katı TR 34662 Altunizade/Üsküdar/İSTANBUL

2/2

OPET.TDS.0705/Rev.03/16.04.2019

Fax :+90 216 522 69 90 teknikservisler@opetfuchs.com.tr opetfuchs.com.tr