

Fullmoto SPR 2T

Optimum Performance for Your 2-Stroke Motorcycle

PRODUCT DESCRIPTION

Fullmoto SPR 2T, is a high performance motorcycle oil which is developed for 2-stroke gasoline engines. Fuel/oil mixing ratio should be decided according to the original equipment recommendations.

CHARACTERISTICS

- Its special additives control soot formation, so keeps engine and its parts clean.
- It provides excellent wear, rust and corrosion protection and long engine life.
- It enables ignition system function properly and improves combustion efficiency.
- In addition to the oil injection systems, it can be used by mixing directly with the fuel.

APPLICATIONS

- It is suitable to use in water or air cooled 2-stroke motorcycles.

PERFORMANCES

- JASO FB
- ISO-L-EGB

TYPICAL PROPERTIES

Densitu@15°C, g/ml	ASTM D 4052	0,878
Viscosity@ 40°C, mm ² /s	ASTM D 445	45,4
Viscosity@100°C, mm ² /s	ASTM D 445	7,1
Viscosity Index	ASTM D 2270	116
Flash Point, °C	ASTM D 92	130
Pour Point, °C	ASTM D 97	-21

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.