

Fullpro HT SYN 10W-40

Approved Performance for Longer Oil Drain Intervals



PRODUCT DESCRIPTION

Fullpro HT SYN 10W-40, is a ultra high performance diesel engine oil for modern heavy commercial vehicles. It offers long oil change interval. The combination of state of the art additive technology with high quality base oils provides excellent oil circulation at cold start, high viscosity index, volatility control and fuel economy.

APPLICATIONS

- It is suitable to use in Euro IV and upper emission standard level engines fitted with Selectively Catalytic Reduction (SCR) and without Diesel Particulate Filter (DPF).

CHARACTERISTICS

- Its advanced additive technology provides excellent engine wear protection under extreme operating conditions.
- Its active cleaning feature controls sludge and deposit formation, thus keeps the engine parts clean and reduces maintenance cost.
- Its superior thermal and oxidation stability maintains its performance during the long oil change interval recommended by the engine manufacturers.
- Its excellent fluidity at cold temperatures protects the engine against wear by providing quick lubrication of engine parts during the first start.

APPROVALS

- DEUTZ DQC IV-10

PERFORMANCES

- ACEA E4/E7
- API CI-4/CH-4/CG-4
- FORD WSS-M2C944-A
- MACK EO-M PLUS
- MAN M 3377/M 3277
- MB-APPROVAL 228.5
- MTU TYPE-3
- RENAULT RLD-2/RLD/RXD
- VOLVO VDS-3

TYPICAL PROPERTIES

| | | |
|-------------------------------------|-------------|-------|
| Density@15°C, g/ml | ASTM D 4052 | 0,861 |
| Viscosity@ 40°C, mm ² /s | ASTM D 445 | 94,3 |
| Viscosity@100°C, mm ² /s | ASTM D 445 | 13,8 |
| Viscosity Index | ASTM D 2270 | 149 |
| Flash Point, °C | ASTM D 92 | 232 |
| Pour Point, °C | ASTM D 5950 | -33 |
| TBN, mgKOH/g | ASTM D 2896 | 13 |

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.