



Fulltech 0W-16

Extra Performance with Significantly Fuel



Economy

PRODUCT DESCRIPTION

Fulltech 0W-16, is a synthetic engine oil that meets the extra performance requirements of high technology gasoline engines. Its special formula provides effective engine cleanlines, low oil consumption, superior engine wear protection and extreme fuel economy.

APPLICATIONS

- It is suitable to use in new technology gasoline and hybrid engines of vehicles espacially Honda and Toyota brands.
- It is suitable to use in naturally aspirated and turbocharged gasoline engines.

CHARACTERISTICS

- It provides excellent wear protection in latest generation and extra performance gasoline engines under all operating and driving conditions.
- Its improved friction characteristics provides extreme fuel economy.
- Its excellent fluidity during cold weather conditions provides quick lubrication of engine parts during the first start up, so protects the engine against wear.
- Its low volatility reduces oil consumption, so helps the decrease of hydrocarbon pollution.

PERFORMANCES

- API SP/ SN PLUS
- ILSAC GF-6B

TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0.843
Viscosity@ 40°C, mm²/s	ASTM D 445	35,5
Viscosity@100°C, mm²/s	ASTM D 445	7,1
Viscosity Index	ASTM D 2270	165
Flash Point, °C	ASTM D 92	220
Pour Point, °C	ASTM D 5950	-45
TBN, mgKOH/g	ASTM D 2896	7,3

OPET.TDS.0008/Rev.00/08.10.2021

MKo<u>c</u>

OPET FUCHS MADENİ YAĞ SamaYİ VE TİCARET A.Ş. Ord. Prof. Dr. Fahrettin Kerim Gökay Cad. Eşref Çakmak Plaza No: 32 Giriş Katı TR 34662 Altunizade/Üsküdar/İSTANBUL

Phone: +90 216 522 69 00 Fax : +90 216 522 69 90 teknikservisler@opetfuchs.com.tr opetfuchs.com.tr

1/2



HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers spesifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.

OPET.TDS.0008/Rev.00/08.10.2021



OPET FUCHS MADENİ YAĞ S 2/2 **/İ VE TİCARET A.Ş.** Ord. Prof. Dr. Fahrettin Kerim Gökay ∟ac. ⊨şref Çakmak Plaza No: 32 Giriş Katı TR 34662 Altunizade/Üsküdar/İSTANBUL

Phone: +90 216 522 69 00 Fax : +90 216 522 69 90 teknikservisler@opetfuchs.com.tr opetfuchs.com.tr