

Fulltech 10W-60

Ultra High Performance Under Extreme Driving And Road Conditions



PRODUCT DESCRIPTION

Fulltech 10W-60, is a synthetic engine oil based on innovative engine oil technology. The modern technology additive technology provides ultra high performance under extreme driving and road conditions. Its special formula offers easy cold starting, highly durable lubricating film and low oil consumption.

APPLICATIONS

- It is suitable to use in new technology gasoline or diesel engines of passenger vehicles and light duty vehicles.
- It is especially recommended for modified or high performance vehicles.

CHARACTERISTICS

- Its durable lubricating film layer reduces friction and wear effectively.
- It has high thermal stability.
- It keeps its oil pressure even at high temperatures.
- Its excellent fluidity during cold weather conditions protects the engine against wear by providing quick lubrication of engine parts during the first start.
- Its low volatility reduces oil consumption, so helps the decrease of hydrocarbon pollution.

PERFORMANCES

- ACEA A3/B3
- API SL/CF

TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0,850
Viscosity@ 40°C, mm ² /s	ASTM D 445	173,0
Viscosity@100°C, mm ² /s	ASTM D 445	23,5
Viscosity Index	ASTM D 2270	175
Flash Point, °C	ASTM D 92	230
Pour Point, °C	ASTM D 97	-36
TBN, mgKOH/g	ASTM D 2896	9,6

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.